



SERVICE & LUBE SKID

BRING PM DIRECTLY TO THE EQUIPMENT



FEATURED MODEL: SLS60

STANDARD FEATURES

TANKS & FRAME

- 10 Gauge Sloped Floor Steel Tanks
- 25, 55, or 115 Gal Tanks
- Stainless Tanks for DEF, Coolant
- Lockable Pump Enclosure
- Spinsecure™ Locking Fuel Caps
- Fluid Level Sight Gauges
- Heavy Duty Steel Frame
- 4x8" Fork Pockets
- Grey Dual Coat Polyurethane Paint

PUMPING SYSTEM

Configurable with either:

- Mi-T-M® Air Compressor, 50' Reel
- Plumbed for External Air Supply



Utility Box and Operator Panel

PNEUMATIC SYSTEM

- 50' Retracting Reel, 1/2" Hose
- Samson® PumpMaster2 1:1 Ratio Pump
- Mechanical Preset Nozzles (Quarts)



FLUID SYSTEM OPTIONS

OIL SYSTEM

- 50' Retracting Reel, 1/2" Hose
- Samson® PumpMaster4 5:1 Ratio Pump, 2.1 GPM*
- Mechanical Preset Nozzles (Quarts)
- Desiccant Tank Vents & Post Pump Filter Option

USED OIL RECLAIM SYSTEM

- 50' Retracting Reel, 1" Hose
- 4-Way Valve to Empty/Fill with Single Pump
- Samson® DP200 Diaphragm Pump
- Able to Connect Multiple Tanks
- Used Filter Drain Box for 2 Filters

COOLANT SYSTEM

- 50' Retracting Reel, 1/2" Hose
- Samson® PumpMaster2 1:1 Ratio Pump, 2.1 GPM
- Mechanical Preset Nozzles (Quarts)

USED COOLANT RECLAIM SYSTEM

- 50' Retracting Reel, 3/4" Hose
- 1:1 Samson® PumpMaster2 Pump
- 4-Way Valve to Empty/Fill with Single Pump
- Able to Connect Multiple Tanks

TOP OFF DIESEL SYSTEM

- 50' Retracting Reel, 1/2" Hose
- 1:1 Samson® PumpMaster2 Pump
- Mechanical Preset Nozzle (Quarts)

GREASE SYSTEM

- 35lb Grease Kit with 50' Retracting Reel, 1/2" Hose
- 120lb Grease Kit with 75' Retracting Reel, 1/2" Hose
- Samson® 55:1 Ratio Pump
- Trigger Nozzle (Quarts)

SPECIFICATIONS

		
Model	SLS460	SLS690
Tank Sizes	25-, 55- or 115-gal (Must total 460 or 690)	
L W H	133" 65" 69"	162" 65" 69"
Empty Weight	4,600 lbs.	5,200 lbs.